

NOUVOL SV

Characteristics

Composition	: Synthetic Sulphited Ester
Appearance	: White, Fluid Paste
Active Content	: 52 ± 1%
pH (1 : 10)	: 7.5 ± 0.5
Emulsions	: Finely Dispersed
Stability	: Excellent
Light Fastness	: Excellent

Inverse Emulsion of water in oil for soft and damp touch.

NOUVOL SV produces an inverse emulsion that is water in oil and not oil in water. This helps in homogenisation and re-distribution of natural fat of leather which otherwise is difficult to achieve with the conventional fatliquoring system.

It makes the leather soft and damp to touch and is completely lightfast. It shows excellent stability to mineral tanning and is recommended for use in tanning or retanning bath where it improves the fixing and life span.

NOUVOL SV should be prepared and applied alone due to its particular properties. It is specifically recommended for use with articles like softy, gloves and double face leathers. It helps in opening up of the structure of treated leathers thus improving the grain smoothness and area.

Usage

Stir before use 

To the required quantity of Nouvol SV, add slowly three times of its own weight of water at 60°C, while stirring constantly.

Caution: Nouvol SV should be prepared and applied alone due to its particular properties.

▪ Re-chroming	1.0-2.0% Nouvol SV
▪ Pre-fatliquoring	1.0-2.0% Nouvol SV
▪ Retanning	1.0% Nouvol SV

Note: Suggested formulations are only for guidance and necessary modifications must be made to achieve a particular result.

Suggested Application

- ✓ Gloving
- ✓ Upholstery
- ✓ Double Face

REACH COMPLIANT



Green-Trek- Compliant

A symbol of our commitment to sustainable technologies

Storage : Store between +5 °c to 35 °c in original pack, well-sealed & stored.
Shelf-life : Product is stable for 6 months from the date of production / Invoice.



Non flammable

Avoid direct contact with skin



Store in dry place

Use Gloves / Ensure Ventilation

