

UTOP MATT

Characteristics of Emulsion

Appearance	: Milky Emulsion
Nature	: Aliphatic Polyurethane Dispersion
Charge	: Anionic
Solid Content	: 17 ± 1%
pH (10% Sol.)	: 9.0 ± 0.5
N. M. P. Content (%)	: Nil
Mechanical Stability	: Good

Characteristics of Film

Appearance	: Opaque and Matt
Light Fastness	: Excellent
Cold-crack Resistance	: Excellent

REACH COMPLIANT



Green-Trek- Compliant

A symbol of our commitment to sustainable technologies

Storage : Store between +5 °C to 35 °C in original pack, well-sealed & stored.
Shelf-life : Product is stable for 6 months from the date of production / Invoice.



Non flammable

Avoid direct contact with skin



Prevent from freezing

Use Gloves / Ensure Ventilation



General Purpose Matt Polyurethane Dispersion with an anti-scratch additive for use as aqueous top coat for elegant look and VOC free finishes on leather.

UTOP MATT is a dull waterborne aliphatic polyurethane dispersion designed for general purpose matt PU finishing. It can also be utilised as a dulling component in base and intermediate coats. Treated leathers will have a pleasant touch, outstanding flexibility, abrasion and scuff resistance. The film properties confer good coverage, uniformity and filling without impairing plating and embossing characteristics.

UTOP MATT can be combined with Urez 785 G for regulating the final gloss on leather. The product can be blended with various feel modifiers to achieve the desired touch. It can be cross-linked with the help of Xama 2 or Xama 7.

Usage

Stir before use 

- Matt Top Coat :

900	parts	Utop MATT
85	parts	Glaze Top N
7	parts	Finish M 45
3	parts	Leveller 168
5	parts	Xama 7
- Low Gloss Top Coat :

500	parts	Utop MATT
495	parts	Urez 785 G
5	parts	Xama 7

IMPORTANT: PROTECT FROM FREEZING.

Note: Suggested formulations are only for guidance and necessary modifications must be made to achieve a particular result.