

## WAX 16/S

## Characteristics

Appearance	: Off White Viscous Liquid
Nature	: Waxes, Proteins & Silicons
Solid Content	: 15 ± 1%
pH (10% Sol.)	: 9.0 ± 0.5
Flexibility	: Good

*WAX 16/S is an outstanding "anti-tack" compound for high quality resin finishes. Contains high performance waxes, proteins and silicones in aqueous medium.*

WAX 16/S is designed for use as sole auxiliary in resin seasons to eliminate tackiness, improve plate release and impart silky waxy touch that is extremely pleasant. It simultaneously affords good levelling action, improves fullness in bottoming coats and reduces tackiness on piling and plating. .

WAX 16/S can also be used on top coats and is highly compatible with modifiers for creating very fine variants in touch. When mixed with MODIFIER CA/2, it gives a more draggy / waxy touch. A slight addition of MODIFIER WS and sprayed as top coat results in leather having more slippery soapy touch.

Usage

Stir before use 

Season Coat	:	100	parts	Pigment - Nano Series
		120	parts	Acril-m X 858
		80	parts	Acril-m S 8/1
		50	parts	Wax 16/S
		100	parts	Urez 898
		50	parts	Glaze Top N
		500	parts	Water

## REACH COMPLIANT



## Green-Trek- Compliant

A symbol of our commitment to sustainable technologies

Storage : Store between +5 °c to 35 °c in original pack, well-sealed & stored.  
Shelf-life : Product is stable for 6 months from the date of production / Invoice.



Non flammable

Avoid direct contact with skin



Prevent from freezing

Use Gloves / Ensure Ventilation



Note: Suggested formulations are only for guidance and necessary modifications must be made to achieve a particular result.